

High Accuracy Adjustable Current-Limited Power Switch

FEATURES

- 25 mΩ High-Side MOSFET
- 4.5A continuous current capability in EMSOP8
- 1.0~4.50 A (typ.) Adjustable Current Limit
- Low Current under OUT shorted GND
- Support single layer PCB layout
- Built-in Soft-Start
- 4.5 ~ 6.5V Single Supply Operation
- Available EMSOP8 package.

APPLICATIONS



- USB Charger
- USB Ports/Hubs
- Set-Top Boxes

DESCRIPTION

UC7441 is a 25mΩ adjustable current limited power switch intended for applications where heavy capacitive loads and short-circuits are likely to be encountered. These devices offer a programmable current-limit threshold between 1.0A and 4.5 A (typ) via an external resistor. The power-switch rise and fall times are controlled to minimize current surges during turn on/off. UC7441 will enter hiccup mode when OUT voltage is less than 2.85V or OTSD. It can significant reduce the output current and reduce thermal effect to the system.

UC7441 devices limit the output current to a safelevel by switching into a constant-current mode when the output load exceeds the current-limit threshold.

PACKAGE AND APPLICATION




ORDING INFORMATION

Part Number	Package Type	Package Qty	Op Temp(°C)	Mark
UC7441	EMSOP8	3000	-40~85	UC7441

High Accuracy Adjustable Current-Limited Power Switch

PINOUT



PIN FUNCTIONS

NO.	NAME	TYPE ⁽¹⁾	DESCRIPTION
1	GND	G	Ground connection
2	RSET	I	External resistor used to set current-limit threshold;
3	IN	P/I	Power supply/Input voltage connected to Power Switch; connect a 1 μ F or greater ceramic capacitor from IN to GND as close to the IC as possible
4	ENB	I	Enable input, logic low turns on UC7441, floating forbidden.
5	NC	NC	No Connected;
6,7,8	OUT	O	Power-switch output, connected to VBUS of USB; connect a 22 μ F or greater ceramic capacitor from OUT to GND as close to the IC as possible; These pins need to be shorted on PCB board;

(1) G = Ground, I = Input, O = Output, P = Power

High Accuracy Adjustable Current-Limited Power Switch

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

Over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		MIN	MAX	UNIT
Supply Voltage Range	IN, OUT, RSET, ENB	-0.3	7.0	V
ESD rating, Human Body Model (HBM)	IN, OUT, RSET, ENB		2	kV
Operating Junction Temperature	T _J	-40	125	°C
Storage Temperature Range	T _{stg}	-65	150	

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

THERMAL CHARACTERISTICS

over operating free-air temperature range (unless otherwise noted)

THERMAL METRIC			UNIT
θ_{JA}	EMSOP8 Package thermal impedance ⁽¹⁾	65	°C/W

(1) The package thermal impedance is calculated in accordance with JESD 51-7.

RECOMMENDED OPERATING CONDITIONS

PARAMETER		MIN	MAX	UNIT
V _{IN}	Input voltage of IN	4.5	6.5	V
V _{OUT}	Output voltage of OUT	4.5	6.5	
R _{SET}	Resistance of R _{SET}	18	100	kΩ
I _{OUT}	Continuous OUT current	1000	4500	mA
T _J	Operating Junction Temperature	-40	125	°C

High Accuracy Adjustable Current-Limited Power Switch

ELECTRICAL CHARACTERISTICS


Conditions are: TA = 25°C, VIN = 5.0 V, ENB = GND and RSET = 33.0 kΩ. Positive current are into pins. All voltages are with respect to GND (unless otherwise noted).

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT	
Power Switch						
R _{DS(on)}	EMSOP8 Package	I _{OUT} =1A		25	mΩ	
Tr	OUT voltage rise time	CL = 1 μF, RL = 100 Ω,		1.73	ms	
Tf	OUT voltage fall time			0.8		
Ton	OUT voltage turn-on time			2.48		
Toff	OUT voltage turn-off time			2.98		
Current Limit						
I _{OS}	OUT current limited	Rset=21.5k	2.42	2.70	3.00	A
		Rset=13.5k	3.68	4.1	4.55	
Enable Pin (ENB)						
V _{ENB}	ENB threshold voltage, falling		0.8	1.33	2.3	V
V _{ENB_HYS}	Hysteresis			150		mV
R _{PD}	Pull Down Resistor		200	290	380	kΩ
Hiccup Mode						
V _{OUT_SHORT}	OUT Threshold Voltage to enter Hiccup mode			2.85		V
T _{ON_HICCUP}	ON Time of Hiccup mode		70	130	190	ms
T _{OFF_HICCUP}	OFF Time of Hiccup mode		0.7	1.3	1.9	s
Thermal Shutdown						
	Temperature Rising Threshold			172		°C
	Hysteresis			20		
UNDERVOLTAGE LOCKOUT						
V _{UVLO}	IN rising UVLO threshold voltage		3.75	3.95	4.15	V
	Hysteresis			100		mV
SUPPLY CURRENT						
I _{IN}	IN supply current	VIN=5.0V, ENB=0V		160	280	μA
I _{INL}	IN Disable Supply Current	VIN=ENB=5.0V		0	2	

High Accuracy Adjustable Current-Limited Power Switch

PACKAGE INFORMATION

EMSOP8



标注	尺寸	最小(mm)	最大(mm)	标注	尺寸	最小(mm)	最大(mm)
A		2.90	3.10	C3		0.152	
A1		0.28	0.35	C4		0.15	0.23
A2		0.65TYP		H		0.02	0.15
A3		0.375TYP		θ		12° TYP4	
B		2.90	3.10	θ1		12° TYP4	
B1		4.70	5.10	θ2		14° TYP	
B2		0.45	0.75	θ3		0° ~ 6°	
C		0.75	0.95	R		0.15TYP	
C1		--	1.10	R1		0.15TYP	
C2		0.328TYP					

* 注: EMSOP8产品框架基高尺寸为1.80X1.80, 散热片尺寸为1.80X1.55 (单位: mm)